

SECUMAX 320
CUTS EVEN BETTER THAN IT LOOKS.



THE SAFER WAY TO CUT.

martor

SECUMAX 320

NO. 32000110




Original size



Safety first

The concealed blade and rounded nose reliably protects you and your products. At the same time, the knife head is designed to ensure that cutting materials optimally reaches the blade.



Blade change made easy

For efficient cutting, make sure to turn or replace the blade regularly: Simply lift up the blade change button and remove the cover. You can then directly access the 4-cutting edge blade.



Perfect ergonomics

The rounded handle fits snugly in your hand for effortless cutting, particularly of film and strapping band. The pre-set cutting angle is also beneficial for your hand and arm and supports you in your tasks.



Optimised blade area

Just two examples: The cutting channel is formed so that your safety knife moves away the freshly cut material even faster. Diagonal cuts are also easier than ever to perform. Your benefits: Less effort required for the task.



Sustainable built

The SECUMAX 320's handle casing is made from at least 80% recycled plastic plus fibreglass. A long service life is also ensured by the high-quality material and first-class build. This also contributes to environmental sustainability.

Film cutter, state-of-the-art.

The environmentally friendly SECUMAX 320 instantly impresses with its award-winning design. Closer examination reveals its inner values. The SECUMAX 320's ergonomic handle casing is made from at least 80% recycled plastic plus fibreglass reinforcement. It has a blade head specially designed for opening film and strapping bands and splitting adhesive tape. Its concealed blade guarantees maximum work safety.

PRODUCT FEATURES

Technical features

	Maximum safety		Safer blade change (with magnet)
	Abrasion resistant		Very ergonomic
	4-cutting edge blade		Cutting depth
	Ceramic blade insertable		Tape splitter
	Soft grip		For right and left handers
	Lanyard hole		Printable for promotional purposes

Main cutting materials

	Wrapping, stretch, and shrink foil		Layers of foil or paper
	Plastic strapping band		Cardboard: 1-ply
	Tape		Bagged goods

Installed blade



NO. 92043 0.40 mm, deep-edged

Optional blade






NO. 92C 0.50 mm, ceramic
NO. 192043 0.40 mm, deep-edged, stainless


Certificates and awards



Application



Safety technology



Concealed blade – a maximum degree of safety

The SECUMAX 320 blade is not an open one, but is hidden from people and goods. This provides you with a maximum degree of safety from cut injuries and from damage to goods.

THE PERFECT FIT FOR ALL.
DOES THE PERFECT JOB.

- SECUMAX 320
- › Concealed blade
 - › Specialist for foils and plastic straps
 - › Handle casing made of recycled plastic
 - › Integrated tape splitter
 - › GS-certified for approved safety

PRODUCT DETAILS

Order No.	NO. 32000110.02	
Packaging unit	1 in single unit box (10 in multipack)	
Knife size (L x W x H)	158 x 13 x 56 mm	
Main material	Recycled plastic, glass fibre reinforced	
Weight	47,4 g	
Cutting depth	4 mm	
Spare blade	NO. 92043.66	
Packaging unit	(10 in safety dispenser)	
Size (L x W x Thickness)	26 x 18.5 x 0.40 mm	
Certified	GS certificate NO. 186513-7809-55094-2023	
Accessories		
BELT HOLSTER M		NO. 9921
BELT HOLSTER XXL		NO. 9924
TOOL RETRACTOR		NO. 9960
USED BLADE CONTAINER		NO. 9810
WALL MOUNT BRACKET USED BLADE CONTAINER		NO. 9845
SAFEBOX		NO. 108000

CONTACT AND SERVICE

What makes our cutting solutions even safer?
Our advisory services! We are always on hand,
to give advice, to provide you with training ma-
terial, to meet with you in person if necessary.

You will find further information on our website:
www.martor.com



At a glance: the safety poster shows the most important functions and correct usage – perfect for your workplace.



From the first cut to changing the blade, our video will show you the best way to use this knife.



Everything you want to know: dimensions, prop-
erties, special features and more about our cutting
tools can be found in the technical data sheet.



Still have questions? You can reach our service
department on [+44 1924 281333](tel:+441924281333)